



**SPECIFICATION DATA SHEET FOR GLASS-LINED APPARATUS**

CLIENT NAME :

PRODUCT NAME :

	BODY	JACKET
NOMINAL VOLUME ( )	( )	—
CONTENTS TO BE USED NAME: PH:	P = (Specific Gravity) M = cps (Viscosity) Slurry wt.% Physical Properties	<input type="checkbox"/> Steam <input type="checkbox"/> Warm Water <input type="checkbox"/> Water <input type="checkbox"/> Cooling Medium <input type="checkbox"/> Heating Medium Physical Properties
DESIGN PRESSURE	Kg/cm <sup>2</sup>	Kg/cm <sup>2</sup>
DESIGN TEMPERATURE	°C	°C
MAX.OPERATING PRESSURE	Kg/cm <sup>2</sup>	Kg/cm <sup>2</sup>
MAX.OPERATING TEMPERATURE	°C	°C
TYPE OF AGITATION	<input type="checkbox"/> Mixing <input type="checkbox"/> Gas Absorption <input type="checkbox"/> Suspension <input type="checkbox"/> Extraction <input type="checkbox"/> Emulsification <input type="checkbox"/> Heat Transfer	
TYPE OF AGITATOR	<input type="checkbox"/> Three-blade Impeller <input type="checkbox"/> Anchor <input type="checkbox"/> Others	
ROTATION SPEED	r.p.m(Revolution per minute)	
TYPE OF SHAFT SEAL	<input type="checkbox"/> Double Mechanical Seal <input type="checkbox"/> Single Mechanical Seal <input type="checkbox"/> Dry Seal <input type="checkbox"/> Gland Seal <input type="checkbox"/> Others (Seal liquid: )	
TYPE OF BAFFLE	<input type="checkbox"/> Finger Baffle <input type="checkbox"/> D-Type Baffle <input type="checkbox"/> Thermo-well	
TYPE OF REDUCER		
SPECIFICATION OF MOTOR	Kw.                      V.                      P.                      Hz <input type="checkbox"/> Safety Increased <input type="checkbox"/> Explosion Proof <input type="checkbox"/> Indoor Type <input type="checkbox"/> Outdoor Type	
CODE	In accordance with JIS B8243	
GOVERNMENT INSPECTION BEFORE SHIPMENT, IF ANY		
SPARE PARTS, IF ANY		
REMARKS		